



PRODUCT SPECIFICATION

5140 D/S PET TAPE

PRODUCT CODE	: 5140
PRODUCT	: D/S Polyester Tape
BACKING	: Polyester Film
LINER	: White Glassine
COLOR	: Transparent
TEMPERATURE RESISTANCE	: 70 °C
ADHESIVE SYSTEM	: Removable Side Acrylic / Permanent side rubber
ADHESION TO STEEL	: 4,8 N / 25 mm (Liner Side) 26,2 N / 25 mm (Unwind Side)
THICKNESS	: 0,074 mm
MAIN CHARACTERISTIC	: It is essential, as with all pressure sensitive tapes, that the surface to which the tape is applied be clean, dry, and free of grease or oil. Bond strength is dependent upon the amount of adhesive-to-surface contact developed Note that different pressure, time and temperature on different (film / rigid) surface achieves different performance.
SHELF LIFE & STORAGE	: Shelf life of the product is 12 months after production. Rolls have to be stored vertically without direct sun contact and in room temperature of 20°C and humidity of 50%.

Elsen self-adhesive tapes are used successfully in many sectors to solve a variety of problems. Our publications contain numerous examples of such uses, intended to help towards a solution of your particular problems. Each Elsen product has been developed for a particular range of applications. Nevertheless, experience has shown that even for one and the same objective, the exact requirements may differ from case to case. We, therefore, recommend that you carry out your own tests in each case, to confirm that Elsen self-adhesive tape which you envisage using is appropriate for your particular application. All information and recommendations are given by us in good faith, on the basis of practical experience,

but without warranty.