



## PRODUCT SPECIFICATION

### 7071 KAPTON (Polyimide) TAPE

PRODUCT CODE	: 7071
PRODUCT	: Kapton (Polyimide) Tape
BACKING	: Kapton (Polyimide)
BACKING THICKNESS	: 0,025 mm
COLOR	: Amber
TEMPERATURE RESISTANCE	: 200 C°
ADHESIVE SYSTEM	: Silicon
ADHESION TO STEEL	: 7,85 N / 25 mm
THICKNESS	: 0,055 mm
ELONGATION AT BREAK	: 55 %
DIELECTRIC STRENGTH	: 7 kV
MAIN CHARACTERISTIC	: High with excellent electrical properties, high heat resistant above 200 °C , flame retardant. Mask-off gold finger contacts during soldering for high temperature masking , insulating , component packaging and high temperature application offlexible circuit board during soaking.

**SHELF LIFE & STORAGE** : Shelf life of the product is 12 months after production. Rolls have to be stored vertically without direct sun contact and in room temperature of 20°C and humidity of 50%.

Elsen self-adhesive tapes are used successfully in many sectors to solve a variety of problems. Our publications contain numerous examples of such uses, intended to help towards a solution of your particular problems. Each Elsen product has been developed for a particular range of applications. Nevertheless, experience has shown that even for one and the same objective, the exact requirements may differ from case to case. We, therefore, recommend that you carry out your own tests in each case, to confirm that Elsen self-adhesive tape which you envisage using is appropriate for your particular application. All information and recommendations are given by us in good faith, on the basis of practical experience, but without warranty.