



PRODUCT SPECIFICATION

5100 D/S POLYESTER TAPE

PRODUCT CODE	: 5100
PRODUCT	: D/S Polyester Tape
BACKING	: Polyester Film
LINER	: RED Siliconised OPP Film
COLOR	: Transparent
TEMPERATURE RESISTANCE	: 90 °C Long Time / 200 °C Short Time
ADHESIVE SYSTEM	: Acrylic
ADHESION TO STEEL	: 24 N / 25 mm
THICKNESS	: 0,22 mm ± 0,05 mm
TACK ROLLING BALL	: > 50 mm
HOLDING POWER :	≥ 24 h / 1kg / 25x25mm
MAIN CHARACTERISTIC	: High initial tack and good resistance to UV rays oxygen and other polluting agents. High degree of transparency. High temperature shear resistance. Excellent adhesion with resistance to fuels , motor oils and solvents.

SHELF LIFE & STORAGE : Shelf life of the product is 12 months after production. Rolls have to be stored vertically without direct sun contact and in room temperature of 20°C and humidity of 50%.

Elsen self-adhesive tapes are used successfully in many sectors to solve a variety of problems. Our publications contain numerous examples of such uses, intended to help towards a solution of your particular problems. Each Elsen product has been developed for a particular range of applications. Nevertheless, experience has shown that even for one and the same objective, the exact requirements may differ from case to case. We, therefore, recommend that you carry out your own tests in each case, to confirm that Elsen self-adhesive tape which you envisage using is appropriate for your particular application. All information and recommendations are given by us in good faith, on the basis of practical experience, but without warranty.