



TECHNICAL DATA

Scapa 2724

PVC Hazard Warning Adhesive Tape

DESCRIPTION

Scapa 2724 is a 0.16mm premium quality soft PVC tape, which uses an aggressive pressure sensitive rubber-based adhesive system. It combines excellent mechanical strength, easy transversal tearability and abrasion resistance with excellent conformability. Available in striped colours only.

APPLICATIONS

- Hazard warning and safety tape
- Identification of potential danger areas

PRODUCT BENEFITS

- Excellent resistance to abrasion, corrosion, and moisture
- Suitable for indoor and protected outdoor environments
- High abrasion and mechanical resistance
- Excellent conformability
- Easy transversal tearability
- Environmentally friendly technology
- Conforms to European Directive 2000/53 EC (lead, chromium VI, mercury, cadmium free)

TECHNICAL PROPERTIES

	Unit	Value	Test Method
Nominal Thickness	mm	0,16	CEI EN 60454
Tensile Strength	N/cm	25	CEI EN 60454
Elongation at Break	%	150	CEI EN 60454
Adhesion to Steel	N/cm	1.5	CEI EN 60454
Adhesion to Backing	N/cm	1.5	CEI EN 60454

STANDARD PRESENTATION

- Roll length: 33 metres
- Roll width: 50, 75 and 100mm
- Core: 76mm Scapa branded cardboard core
- Packaging: Heat shrink sleeve
- Colours: (Striped) Yellow/black, White/red

RECOMMENDATIONS

Rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. The storage temperature should be between +10°C and +25°C. Use within 24 months

The tape should be applied with sufficient pressure to ensure optimum bonding and prevent flagging effects.

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.