



PRODUCT SPECIFICATION

5120 D/S SIDED POLYESTER TAPE

PRODUCT CODE	: 5120
PRODUCT	: Double Sided Polyester Tape
BACKING	: Polyester Film
BACKING THICKNESS	: 0,012 mm
LINER	: PE Coated Bleached Kraft Paper
COLOR	: Transparent
TEMPERATURE RESISTANCE	: - 20 °C / 80 °C
ADHESIVE SYSTEM	: Solvent Based Acrylic
ADHESION TO STEEL	: 12 N / 25 mm
THICKNESS	: 0,09 mm ± 0,005
HOLDING POWER	: ≥ 24 h / 1kg / 25x25mm
MAIN CHARACTERISTIC	: Suitable for clean removal needs. General purpose industrial applications – for bonding , fixing , mounting & splicing. Mounting of nameplates, trophies and signs. Bonding of sporting goods – tennis, shoes , leather, etc

SHELF LIFE & STORAGE : Shelf life of the product is 12 months after production. Rolls have to be stored vertically without direct sun contact and in room temperature of 20°C and humidity of 50%.

Elsen self-adhesive tapes are used successfully in many sectors to solve a variety of problems. Our publications contain numerous examples of such uses, intended to help towards a solution of your particular problems. Each Elsen product has been developed for a particular range of applications. Nevertheless, experience has shown that even for one and the same objective, the exact requirements may differ from case to case. We, therefore, recommend that you carry out your own tests in each case, to confirm that Elsen self-adhesive tape which you envisage using is appropriate for your particular application. All information and recommendations are given by us in good faith, on the basis of practical experience, but without warranty.