



PRODUCT SPECIFICATION

4808GF ACRYLIC FOAM TAPE

PRODUCT CODE	: 4808GF
PRODUCT	: Acrylic Foam Tape
LINER	: Red PE
COLOR	: Gray
TEMPERATURE RESISTANCE	: 160 °C (Short Term) 100 °C (Long Term.)
ADHESIVE SYSTEM	: Acrylic
ADHESION TO STEEL	: 18 N / 25 mm
THICKNESS	: 0,80 mm± 0,05 mm
TENSILE STRENGTH	: 24 N / 25 mm
HOLDING POWER	: ≥ 24 h / 1kg / 25x25mm
MAIN CHARACTERISTIC	: High performance bonding products, designed to provide engineered assembly solutions for a wide variety of industrial applications. They are ideal for replacing mechanical fasteners and liquid adhesives in permanent applications where a very high strength bond is required

SHELF LIFE & STORAGE : Shelf life of the product is 12 months after production. Rolls have to be stored vertically without direct sun contact and in room temperature of 20°C and humidity of 50%.

Elsen self-adhesive tapes are used successfully in many sectors to solve a variety of problems. Our publications contain numerous examples of such uses, intended to help towards a solution of your particular problems. Each Elsen product has been developed for a particular range of applications. Nevertheless, experience has shown that even for one and the same objective, the exact requirements may differ from case to case. We, therefore, recommend that you carry out your own tests in each case, to confirm that Elsen self-adhesive tape which you envisage using is appropriate for your particular application. All information and recommendations are given by us in good faith, on the basis of practical experience, but without warranty.