



PRODUCT SPECIFICATION

5408 TRANSFER TAPE

PRODUCT CODE	: 5408
PRODUCT	: Transfer Tape
BACKING	: No Backing
LINER	: Havana Brown Glassine
TEMPERATURES RESISTANCE	: - 40°C up to +140°C
ADHESIVE SYSTEM	: Solvent-Free Modified Acrylic
ADHESION TO STEEL	: 6,80 N / 25 mm
THICKNESS	: 0,08 mm
MAIN CHARACTERISTIC	: General purpose foam bonding e.g. gaskets, sound deadening and insulation materials. End uses involving critical temperature performance e.g. interior automotive trim, PU foams , felts , fabrics, fibres.

SHELF LIFE & STORAGE : Shelf life of the product is 12 months after production. Rolls have to be stored vertically without direct sun contact and in room temperature of 20°C and humidity of 50%.

Elsen self-adhesive tapes are used successfully in many sectors to solve a variety of problems. Our publications contain numerous examples of such uses, intended to help towards a solution of your particular problems. Each Elsen product has been developed for a particular range of applications. Nevertheless, experience has shown that even for one and the same objective, the exact requirements may differ from case to case. We, therefore, recommend that you carry out your own tests in each case, to confirm that Elsen self-adhesive tape which you envisage using is appropriate for your particular application. All information and recommendations are given by us in good faith, on the basis of practical experience,

but without warranty.