



PRODUCT SPECIFICATION

5115 D/S POLYESTER TAPE

PRODUCT CODE	: 5115
PRODUCT	: D/S Polyester Film Tape
BACKING	: Polyester Film
LINER	: RED Siliconised OPP Film
COLOR	: Transparent
TEMPERATURE RESISTANCE	: 90 C° Long time
ADHESIVE SYSTEM	: Acrylic
ADHESION TO STEEL	: 14,6 N / 25 mm
THICKNESS	: 0,16 mm ± 0,05 mm
TACK ROLLING BALL	: > 150 mm
HOLDING POWER :	≥ 24 h / 1kg / 25x25mm
MAIN CHARACTERISTIC	: This tape has a strong Mylar base with a high tack solvent acrylic adhesive giving it excellent holding power and adhesion. Good resistance to weather conditions, UV, plasticizers and aging. The MOPP liner enhances transparency of the adhesive.

SHELF LIFE & STORAGE : Shelf life of the product is 12 months after production. Rolls have to be stored vertically without direct sun contact and in room temperature of 20°C and humidity of 50%.

Elsen self-adhesive tapes are used successfully in many sectors to solve a variety of problems. Our publications contain numerous examples of such uses, intended to help towards a solution of your particular problems. Each Elsen product has been developed for a particular range of applications. Nevertheless, experience has shown that even for one and the same objective, the exact requirements may differ from case to case. We, therefore, recommend that you carry out your own tests in each case, to confirm that Elsen self-adhesive tape which you envisage using is appropriate for your particular application. All information and recommendations are given by us in good faith, on the basis of practical experience, but without warranty.