



PRODUCT SPECIFICATION

2030 SURFACE PROTECTION TAPE

PRODUCT CODE	: 2030
PRODUCT	: Protection Tape
BACKING	: LDPE
COLOR	: Transparent
ADHESIVE SYSTEM	: Acrylic Adhesive
ADHESION TO STEEL	: 2,4 N / 25 mm
THICKNESS	: 0,030 mm
ELONGATION AT BREAK	: 200 %
RESISTANCE	
against moisture	: good
against oil	: moderate
against solvents	: moderate
against UV	: no, only for indoor application
MAIN CHARACTERISTIC	: The film is recommended for the protection of sensitive surfaces against dirt and damage during processing, storage and mounting e.g.

SHELF LIFE & STORAGE : Shelf life of the product is 12 months after production. Rolls have to be stored vertically without direct sun contact and in room temperature of 20°C and humidity of 50%.

Elsen self-adhesive tapes are used successfully in many sectors to solve a variety of problems. Our publications contain numerous examples of such uses, intended to help towards a solution of your particular problems. Each Elsen product has been developed for a particular range of applications. Nevertheless, experience has shown that even for one and the same objective, the exact requirements may differ from case to case. We, therefore, recommend that you carry out your own tests in each case, to confirm that Elsen self-adhesive tape which you envisage using is appropriate for your particular application. All information and recommendations are given by us in good faith, on the basis of practical experience, but without warranty.